



Providing durable, attractive and economical electrical/data solutions

TWO GANG HINGED TOP (5x5) OUTLET BOX WITHOUT INTEGRAL BASE

20-30 AMP MAX

MATERIAL	
PEDESTAL	14 GAUGE STAINLESS STEEL
COVER (WELDED TO PEDESTAL)	14 GAUGE STAINLESS STEEL

DIMENSIONS	
PEDESTAL WIDTH	6.3"
PEDESTAL DEPTH	5.25"
POST DIMENSION	5" x 5"
HEIGHTS AVAILABLE	42", 48" or 54"

FEATURES/ACCESSORIES INCLUDED

UL LISTED, RATED NEMA 3R (RAINPROOF), 20- 30 Amp Max

- LOCKABLE WHILE IN-USE, BUILT-IN, STAINLESS STEEL COVER
- SPACING BETWEEN COVER AND PEDESTAL TO ALLOW CORDS TO SAFELY PASS WHILE LOCKED
- OPEN BOTTOM FOR CONDUIT RACEWAYS: 2 CONDUIT RACEWAYS 1-1/2" EA. MAX. THROUGH THE BOTTOM OR 1" THROUGH THE SIDES
- REMOVABLE ACCESS PANEL FOR WIRING INSTALLATION
- WIRE SLOT OPENINGS ON TWO LOWER SIDES
- GROUND CONDUCTOR TERMINAL PROVIDED AND INSTALLED
- MAY BE DIVIDED FOR HIGH/LOW VOLTAGE
 - WELDED DIVIDING BRACKET INSIDE THE HOUSING
 - AN INSTALLED SECOND GROUND CONDUCTOR TERMINAL
 - ADDITIONAL CUTOUTS ON DEVICE MOUNTING PLATE FOR LOW VOLTAGE
- REMOVABLE RECEPTACLE MOUNTING PLATE
- MUST BE BURIED 24" DEEP

FINISHES
POWDER COATED IN STANDARD COLORS: BLACK, GRAY, GREEN OR BROWN
POWDER COATED IN CUSTOM COLOR FOR AN ADDED FEE (PAINT CHIP REQ'D)
BRUSHED STAINLESS STEEL