

PRODUCT CATALOG

Pedestals for Outdoor Circuits

Safely and conveniently bringing power to the outdoors

As the demand for outdoor power increases, Pedoc power pedestals provide an ideal solution for safely and conveniently bringing power to any outdoor location. The Pedoc product line, thoughtfully designed and developed by a team of electricians and metal fabrication experts, has become the go-to solution for bringing power to even the harshest environments.

Thousands of Pedocs can be found in environments ranging from campgrounds and public parks to apartment complexes and airports to provide standalone power when traditional outlets are unavailable or impractical. Common uses include powering equipment, consumer electronic devices, electric vehicles, engine block heaters, outdoor motors and holiday displays.



Stock and Quick
Ship Options

cULus Listed: Standard 1773 | Rated NEMA 3R
Made in the USA



Overview

Safely and conveniently bringing power to the outdoors

cULus Listed: Standard 1773. Rated NEMA 3R. ADA compliant heights available.

Features and Benefits

Solidly Constructed for Outdoor Use

- Available in powder coated finishes for added UV and scratch protection
- Welded construction from heavy gauge 304 stainless steel to withstand harsh environments
- Optional to upgrade to 316 stainless
- No spare parts needed – ever!

Quick and Easy Installation

- Place over stubbed up conduits
- Pull wiring through the pedestal
- Terminate wiring and install receptacles
- Mount in place

Critical Considerations

- UL listed in USA and Canada
- NEMA 3R rated for use in outdoor locations
- Proudly Made in the USA
- ADA compliant heights available

Variety & Custom Options

- Hundreds of configurations and many finish options
- Standard and custom finishes available



Standard Series

Pre-drilled mounting holes for devices and covers

Direct Bury



With Integral Base



Hinge Top Series

Durable stainless steel cover with locking tab to prevent unauthorized use

5x5 Direct Bury 1-Gang Direct Bury

4x4 Flush Mount



1-Gang with Integral Base



5x5 with Integral Base



Commonly powering:

Outdoor maintenance equipment • Diesel engine block heaters • Holiday lighting • Commercial yard landscaping • Pool pump motors • Emergency shutoffs • Food trucks • Scoreboards and reporting booths • Laptops • Phones and other personal devices • Golf carts

Popular Settings:

Balconies • Airports • Pool Areas • Commercial Parking Lots • Pools and Spas • Amusement Parks • Festivals • Street Fairs • Amenity Decks • Campgrounds • Golf Courses • Marinas • Stadiums • College and corporate campuses

Finishes

Black (B)

Gray (G)

Bronze (BRZ)

Green (GN)

Brown (BR)

Custom (CSTM)

Brushed S.S. (SS)

Flush Mount Hinge Top

Unobtrusive design for areas with limited space

cULus Listed: Standard 1773. Rated NEMA 3R. ADA compliant heights available.

New! 4x4 Flush Mount Hinge Top

1-, 2-gang (up to 20 amp devices)






With an internal mounting bracket and welded cover, this sleek and sturdy model can be placed flush to outdoor structures. Safely and conveniently bringing power while blending perfectly into areas where space is limited.

Welded hinge cover prevents ingress of water from outdoor elements. Solid construction saves on costly repair and replacement maintenance.

- Internal bracketing allows for flush mount applications
- Self-closing cover prevents ingress of water from outdoor elements
- Locking tab to prevent unwanted use
- Heavy stainless steel welded construction

Part Numbering

Device Mtg. Plate	Finish	12" Height	18" Height	24" Height	30" Height
	Black	4FMIM12-C-HT-B-1	4FMIM18-C-HT-B-1	4FMIM24-C-HT-B-1	4FMIM30-C-HT-B-1
	Gray	4FMIM12-C-HT-G-1	4FMIM18-C-HT-G-1	4FMIM24-C-HT-G-1	4FMIM30-C-HT-G-1
	Bronze	4FMIM12-C-HT-BRZ-1	4FMIM18-C-HT-BRZ-1	4FMIM24-C-HT-BRZ-1	4FMIM30-C-HT-BRZ-1
	Green	4FMIM12-C-HT-GN-1	4FMIM18-C-HT-GN-1	4FMIM24-C-HT-GN-1	4FMIM30-C-HT-GN-1
	Brown	4FMIM12-C-HT-BR-1	4FMIM18-C-HT-BR-1	4FMIM24-C-HT-BR-1	4FMIM30-C-HT-BR-1
	Custom	4FMIM12-C-HT-CSTM-1	4FMIM18-C-HT-CSTM-1	4FMIM24-C-HT-CSTM-1	4FMIM30-C-HT-CSTM-1
	Brushed S.S.	4FMIM12-SS-HT-1	4FMIM18-SS-HT-1	4FMIM24-SS-HT-1	4FMIM30-SS-HT-1
	Black	4FMIM12-C-HT-B-2	4FMIM18-C-HT-B-2	4FMIM24-C-HT-B-2	4FMIM30-C-HT-B-2
	Gray	4FMIM12-C-HT-G-2	4FMIM18-C-HT-G-2	4FMIM24-C-HT-G-2	4FMIM30-C-HT-G-2
	Bronze	4FMIM12-C-HT-BRZ-2	4FMIM18-C-HT-BRZ-2	4FMIM24-C-HT-BRZ-2	4FMIM30-C-HT-BRZ-2
	Green	4FMIM12-C-HT-GN-2	4FMIM18-C-HT-GN-2	4FMIM24-C-HT-GN-2	4FMIM30-C-HT-GN-2
	Brown	4FMIM12-C-HT-BR-2	4FMIM18-C-HT-BR-2	4FMIM24-C-HT-BR-2	4FMIM30-C-HT-BR-2
	Custom	4FMIM12-C-HT-CSTM-2	4FMIM18-C-HT-CSTM-2	4FMIM24-C-HT-CSTM-2	4FMIM30-C-HT-CSTM-2
	Brushed S.S.	4FMIM12-SS-HT-2	4FMIM18-SS-HT-2	4FMIM24-SS-HT-2	4FMIM30-SS-HT-2
	Black	4FMIM12-C-D-HT-B-2	4FMIM18-C-D-HT-B-2	4FMIM24-C-D-HT-B-2	4FMIM30-C-D-HT-B-2
	Gray	4FMIM12-C-D-HT-G-2	4FMIM18-C-D-HT-G-2	4FMIM24-C-D-HT-G-2	4FMIM30-C-D-HT-G-2
	Bronze	4FMIM12-C-D-HT-BRZ-2	4FMIM18-C-D-HT-BRZ-2	4FMIM24-C-D-HT-BRZ-2	4FMIM30-C-D-HT-BRZ-2
	Green	4FMIM12-C-D-HT-GN-2	4FMIM18-C-D-HT-GN-2	4FMIM24-C-D-HT-GN-2	4FMIM30-C-D-HT-GN-2
	Brown	4FMIM12-C-D-HT-BR-2	4FMIM18-C-D-HT-BR-2	4FMIM24-C-D-HT-BR-2	4FMIM30-C-D-HT-BR-2
	Custom	4FMIM12-C-D-HT-CSTM-2	4FMIM18-C-D-HT-CSTM-2	4FMIM24-C-D-HT-CSTM-2	4FMIM30-C-D-HT-CSTM-2
	Brushed S.S.	4FMIM12-SS-D-HT-2	4FMIM18-SS-D-HT-2	4FMIM24-SS-D-HT-2	4FMIM30-SS-D-HT-2

Personal device



Finishes

Black (B)

Gray (G)

Bronze (BRZ)

Green (GN)

Brown (BR)

Custom (CSTM)

Brushed S.S. (SS)

Specifications

Material	304 Stainless Steel: 14-gauge body; optional upgrade to 316
Construction	Welded pedestal body, base, and weatherproof cover (lockable)
Finishes	Outdoor rated powder coat paint (standard and custom), brushed stainless
Heights	12", 18", 24", 30"
Dimensions	4" wide by 4" deep pedestal with 4-1/4" wide by 5" deep cover
Devices	Not supplied; can accommodate 15 – 20A NEMA rated receptacles (must be weather-resistant)
Device Mount	Removable GFCI device mounting plate insert included
Cover	Auto-closing cover provides protection to meet while-in-use requirements
Hardware	Pre-installed SS grounding hardware; anchoring hardware included
Application	May be ordered with a divider for high and low voltage (data)
Customization	Custom powder coat options
Installation	Open base to accommodate two 1-1/2" conduit raceways
Additional	12" height for non-3-R installations only

Hinge Top with Integral Base: Hardscape

Sleek design for everyday powering



cULus Listed: Standard 1773. Rated NEMA 3R. ADA compliant heights available.

Hinge Top with Integral Base

1-gang (up to 20 amp devices)



Self-closing tamperproof cover prohibits unauthorized use.

Material	304 Stainless Steel: 14-gauge body, 7-gauge base; optional upgrade to 316
Construction	Welded pedestal body, base and weatherproof cover (lockable)
Finishes	Outdoor rated powder coat paint (standard and custom), brushed stainless
Heights	18", 24", 30", 36", 42", 48"
Dimensions	2-1/2" wide by 4" deep pedestal; 2-3/4" wide by 6" deep cover; 8" diameter base
Devices	Not supplied; can accommodate 15 – 20A NEMA rated receptacles (must be weather-resistant)
Device Mount	Removable GFCI device mounting plate insert included
Cover	Auto-closing cover provides protection to meet while-in-use requirements
Hardware	Pre-installed SS grounding hardware; anchoring hardware included
Customization	Custom powder coat options
Installation	Open base to accommodate two 1-1/2" conduit raceways

Perfect for powering tree lighting



Special Features

- Self-closing cover prevents ingress of water from outdoor elements
- Locking hole to prohibit unwanted use
- Completely welded stainless construction
- Concrete stainless steel anchors included
- Spacing between cover and pedestal to allow wiring to pass while-in-use




Part Numbering

Device Mtg. Plate	Finish	18" Height	24" Height	30" Height	36" Height	42" Height	48" Height
	Black	1P18-C-HT-B	1P24-C-HT-B	1P30-C-HT-B	1P36-C-HT-B	1P42-C-HT-B	1P48-C-HT-B
	Gray	1P18-C-HT-G	1P24-C-HT-G	1P30-C-HT-G	1P36-C-HT-G	1P42-C-HT-G	1P48-C-HT-G
	Bronze	1P18-C-HT-BRZ	1P24-C-HT-BRZ	1P30-C-HT-BRZ	1P36-C-HT-BRZ	1P42-C-HT-BRZ	1P48-C-HT-BRZ
	Green	1P18-C-HT-GN	1P24-C-HT-GN	1P30-C-HT-GN	1P36-C-HT-GN	1P42-C-HT-GN	1P48-C-HT-GN
	Brown	1P18-C-HT-BR	1P24-C-HT-BR	1P30-C-HT-BR	1P36-C-HT-BR	1P42-C-HT-BR	1P48-C-HT-BR
	Custom	1P18-C-HT-CSTM	1P24-C-HT-CSTM	1P30-C-HT-CSTM	1P36-C-HT-CSTM	1P42-C-HT-CSTM	1P48-C-HT-CSTM
	Brushed S.S.	1P18-SS-HT	1P24-SS-HT	1P30-SS-HT	1P36-SS-HT	1P42-SS-HT	1P48-SS-HT

Note: The divided models have recently been discontinued. If you cannot find a part number, [click here](#) for a cross-reference alternate guide.



Finishes



5x5 Hinge Top With Integral Base Base: Hardscape

Wider body for dual charging

cULus Listed: Standard 1773. Rated NEMA 3R. ADA compliant heights available.


5x5 Hinge Top with Integral Base


1-, 2-gang (up to 60 amp devices)




Material	304 Stainless Steel: 14-gauge body, 7-gauge base; optional upgrade to 316
Construction	Welded pedestal body, base and weatherproof cover (lockable)
Finishes	Outdoor rated powder coat paint (standard and custom), brushed stainless
Heights	18", 24", 30", 36", 42", 48"
Dimensions	5" wide by 5" deep pedestal; 5-1/4" wide by 6-1/4" deep cover, 8-1/2" diameter base
Devices	Not supplied; For 15-20A devices, weather-resistance devices must be used; devices that are 30-60A must be water-tight
Device Mount	Removable GFCI device mounting plate insert included
Cover	Auto-closing cover provides protection to meet while-in-use requirements for 15 and 20A devices; for aesthetics only when used with 30 - 60A devices
Hardware	Pre-installed SS grounding hardware; concrete anchoring hardware included
Application	May be ordered with a divider for high and low voltage (data)
Customization	Custom powder coat options

Part Numbering (power only applications)

Device Plate Included	Hgt.	Powder Coat ("C")	Brushed SS ("SS")
20A PED0140 	18"	5P18-C-HT-* -140	5P18-SS-HT-140
	24"	5P24-C-HT-* -140	5P24-SS-HT-140
	30"	5P30-C-HT-* -140	5P30-SS-HT-140
	36"	5P36-C-HT-* -140	5P36-SS-HT-140
	42"	5P42-C-HT-* -140	5P42-SS-HT-140
	48"	5P48-C-HT-* -140	5P48-SS-HT-140

30A: PED0142 (1-9/16" dia.) 	18"	5P18-C-HT-* -142	5P18-SS-HT-142
	24"	5P24-C-HT-* -142	5P24-SS-HT-142
	30"	5P30-C-HT-* -142	5P30-SS-HT-142
	36"	5P36-C-HT-* -142	5P36-SS-HT-142
	42"	5P42-C-HT-* -142	5P42-SS-HT-142
	48"	5P48-C-HT-* -142	5P48-SS-HT-142

50/60A PED0154 	18"	5P18-C-HT-* -154	5P18-SS-HT-154
	24"	5P24-C-HT-* -154	5P24-SS-HT-154
	30"	5P30-C-HT-* -154	5P30-SS-HT-154
	36"	5P36-C-HT-* -154	5P36-SS-HT-154
	42"	5P42-C-HT-* -154	5P42-SS-HT-154
	48"	5P48-C-HT-* -154	5P48-SS-HT-154


***insert powder coat finish code:**


B = black, G = gray, BRZ = bronze, GN = green, BR = brown, CSTM - custom

Note: Part numbers have recently been updated, and the side divided models have been discontinued. If you cannot find a part number, [click here](#) for a cross-reference guide.


Finishes


Black (B)	Gray (G)	Bronze (BRZ)	Green (GN)	Brown (BR)	Custom (CSTM)	Brushed S.S. (SS)
-----------	----------	--------------	------------	------------	---------------	-------------------

Device Plate Included	Height	Powder Coat ("C")	Brushed SS ("SS")
20, 30A PED0144 	18"	5P18-C-HT-* -144	5P18-SS-HT-144
	24"	5P24-C-HT-* -144	5P24-SS-HT-144
	30"	5P30-C-HT-* -144	5P30-SS-HT-144
	36"	5P36-C-HT-* -144	5P36-SS-HT-144
	42"	5P42-C-HT-* -144	5P42-SS-HT-144
	48"	5P48-C-HT-* -144	5P48-SS-HT-144

30A: PED0148 (2-1/8" dia.) 	18"	5P18-C-HT-* -148	5P18-SS-HT-148
	24"	5P24-C-HT-* -148	5P24-SS-HT-148
	30"	5P30-C-HT-* -148	5P30-SS-HT-148
	36"	5P36-C-HT-* -148	5P36-SS-HT-148
	42"	5P42-C-HT-* -148	5P42-SS-HT-148
	48"	5P48-C-HT-* -148	5P48-SS-HT-148

Part Numbering (divided for high and low voltage)

Device Plate Included	Hgt.	Powder Coat ("C")	Brushed SS ("SS")
20A PED0140 	18"	5P18-C-D-HT-* -140	5P18-SS-D-HT-140
	24"	5P24-C-D-HT-* -140	5P24-SS-D-HT-140
	30"	5P30-C-D-HT-* -140	5P30-SS-D-HT-140
	36"	5P36-C-D-HT-* -140	5P36-SS-D-HT-140
	42"	5P42-C-D-HT-* -140	5P42-SS-D-HT-140
	48"	5P48-C-D-HT-* -140	5P48-SS-D-HT-140

Device Plate Included	Height	Powder Coat ("C")	Brushed SS ("SS")
20, 30A PED0144 	18"	5P18-C-D-HT-* -144	5P18-SS-D-HT-144
	24"	5P24-C-D-HT-* -144	5P24-SS-D-HT-144
	30"	5P30-C-D-HT-* -144	5P30-SS-D-HT-144
	36"	5P36-C-D-HT-* -144	5P36-SS-D-HT-144
	42"	5P42-C-D-HT-* -144	5P42-SS-D-HT-144
	48"	5P48-C-D-HT-* -144	5P48-SS-D-HT-144

Standard with Integral Base: Hardscape

Higher amperage with multiple device mounting configurations

cULus Listed: Standard 1773. Rated NEMA 3R. ADA compliant heights available.

Standard with Integral Base

1-, 2-gang (up to 60 amp devices)



Material	304 Stainless Steel: 14-gauge body, 7-gauge base; optional upgrade to 316
Construction	Welded pedestal body and integral base
Finishes	Outdoor rated powder coat paint (standard and custom), brushed stainless
Heights	6", 12", 18", 24", 30", 36", 42", 48"
Dimensions	5" wide by 2-1/2" deep; 8" diameter base
Devices	Devices not supplied; 15-20A devices must be weather-resistant and used with an in-use cover; 30-60A devices must be watertight
Covers	Mounting holes for weatherproof covers provided; covers not supplied
Hardware	Pre-installed SS grounding hardware; concrete anchoring hardware included
Application	May be ordered with a divider for high and low voltage (data) devices
Customization	Option for custom colors
Installation	Open base to accommodate two 1-1/2" conduit raceways
Additional	6" and 12" heights suitable for non-3R installations only

Part Numbering

Device Opening	Finish	6" Height	12" Height	18" Height	24" Height	30" Height	36" Height	42" Height	48" Height
1-Gang Horiz. (HZ) 	Black	1P6-C-HZ-B	1P12-C-HZ-B	1P18-C-HZ-B	1P24-C-HZ-B	1P30-C-HZ-B	1P36-C-HZ-B	1P42-C-HZ-B	1P48-C-HZ-B
	Gray	1P6-C-HZ-G	1P12-C-HZ-G	1P18-C-HZ-G	1P24-C-HZ-G	1P30-C-HZ-G	1P36-C-HZ-G	1P42-C-HZ-G	1P48-C-HZ-G
	Bronze	1P6-C-HZ-BRZ	1P12-C-HZ-BRZ	1P18-C-HZ-BRZ	1P24-C-HZ-BRZ	1P30-C-HZ-BRZ	1P36-C-HZ-BRZ	1P42-C-HZ-BRZ	1P48-C-HZ-BRZ
	Green	1P6-C-HZ-GN	1P12-C-HZ-GN	1P18-C-HZ-GN	1P24-C-HZ-GN	1P30-C-HZ-GN	1P36-C-HZ-GN	1P42-C-HZ-GN	1P48-C-HZ-GN
	Brown	1P6-C-HZ-BR	1P12-C-HZ-BR	1P18-C-HZ-BR	1P24-C-HZ-BR	1P30-C-HZ-BR	1P36-C-HZ-BR	1P42-C-HZ-BR	1P48-C-HZ-BR
	Custom	1P6-C-HZ-CSTM	1P12-C-HZ-CSTM	1P18-C-HZ-CSTM	1P24-C-HZ-CSTM	1P30-C-HZ-CSTM	1P36-C-HZ-CSTM	1P42-C-HZ-CSTM	1P48-C-HZ-CSTM
	Brushed S.S.	1P6-SS-HZ	1P12-SS-HZ	1P18-SS-HZ	1P24-SS-HZ	1P30-SS-HZ	1P36-SS-HZ	1P42-SS-HZ	1P48-SS-HZ
1-Gang Vert. (V) 	Black	1P6-C-V-B	1P12-C-V-B	1P18-C-V-B	1P24-C-V-B	1P30-C-V-B	1P36-C-V-B	1P42-C-V-B	1P48-C-V-B
	Gray	1P6-C-V-G	1P12-C-V-G	1P18-C-V-G	1P24-C-V-G	1P30-C-V-G	1P36-C-V-G	1P42-C-V-G	1P48-C-V-G
	Bronze	1P6-C-V-BRZ	1P12-C-V-BRZ	1P18-C-V-BRZ	1P24-C-V-BRZ	1P30-C-V-BRZ	1P36-C-V-BRZ	1P42-C-V-BRZ	1P48-C-V-BRZ
	Green	1P6-C-V-GN	1P12-C-V-GN	1P18-C-V-GN	1P24-C-V-GN	1P30-C-V-GN	1P36-C-V-GN	1P42-C-V-GN	1P48-C-V-GN
	Brown	1P6-C-V-BR	1P12-C-V-BR	1P18-C-V-BR	1P24-C-V-BR	1P30-C-V-BR	1P36-C-V-BR	1P42-C-V-BR	1P48-C-V-BR
	Custom	1P6-C-V-CSTM	1P12-C-V-CSTM	1P18-C-V-CSTM	1P24-C-V-CSTM	1P30-C-V-CSTM	1P36-C-V-CSTM	1P42-C-V-CSTM	1P48-C-V-CSTM
	Brushed S.S.	1P6-SS-V	1P12-SS-V	1P18-SS-V	1P24-SS-V	1P30-SS-V	1P36-SS-V	1P42-SS-V	1P48-SS-V
2-Gang 	Black	2P6-C-B	2P12-C-B	2P18-C-B	2P24-C-B	2P30-C-B	2P36-C-B	2P42-C-B	2P48-C-B
	Gray	2P6-C-G	2P12-C-G	2P18-C-G	2P24-C-G	2P30-C-G	2P36-C-G	2P42-C-G	2P48-C-G
	Bronze	2P6-C-BRZ	2P12-C-BRZ	2P18-C-BRZ	2P24-C-BRZ	2P30-C-BRZ	2P36-C-BRZ	2P42-C-BRZ	2P48-C-BRZ
	Green	2P6-C-GN	2P12-C-GN	2P18-C-GN	2P24-C-GN	2P30-C-GN	2P36-C-GN	2P42-C-GN	2P48-C-GN
	Brown	2P6-C-BR	2P12-C-BR	2P18-C-BR	2P24-C-BR	2P30-C-BR	2P36-C-BR	2P42-C-BR	2P48-C-BR
	Custom	2P6-C-CSTM	2P12-C-CSTM	2P18-C-CSTM	2P24-C-CSTM	2P30-C-CSTM	2P36-C-CSTM	2P42-C-CSTM	2P48-C-CSTM
	Brushed S.S.	2P6-SS	2P12-SS	2P18-SS	2P24-SS	2P30-SS	2P36-SS	2P42-SS	2P48-SS
2-Gang Div. (high/low volt) 	Black	2P6-C-D-B	2P12-C-D-B	2P18-C-D-B	2P24-C-D-B	2P30-C-D-B	2P36-C-D-B	2P42-C-D-B	2P48-C-D-B
	Gray	2P6-C-D-G	2P12-C-D-G	2P18-C-D-G	2P24-C-D-G	2P30-C-D-G	2P36-C-D-G	2P42-C-D-G	2P48-C-D-G
	Bronze	2P6-C-D-BRZ	2P12-C-D-BRZ	2P18-C-D-BRZ	2P24-C-D-BRZ	2P30-C-D-BRZ	2P36-C-D-BRZ	2P42-C-D-BRZ	2P48-C-D-BRZ
	Green	2P6-C-D-GN	2P12-C-D-GN	2P18-C-D-GN	2P24-C-D-GN	2P30-C-D-GN	2P36-C-D-GN	2P42-C-D-GN	2P48-C-D-GN
	Brown	2P6-C-D-BR	2P12-C-D-BR	2P18-C-D-BR	2P24-C-D-BR	2P30-C-D-BR	2P36-C-D-BR	2P42-C-D-BR	2P48-C-D-BR
	Custom	2P6-C-D-CSTM	2P12-C-D-CSTM	2P18-C-D-CSTM	2P24-C-D-CSTM	2P30-C-D-CSTM	2P36-C-D-CSTM	2P42-C-D-CSTM	2P48-C-D-CSTM
	Brushed S.S.	2P6-SS-D	2P12-SS-D	2P18-SS-D	2P24-SS-D	2P30-SS-D	2P36-SS-D	2P42-SS-D	2P48-SS-D



Finishes

Black (B)	Gray (G)	Bronze (BRZ)	Green (GN)	Brown (BR)	Custom (CSTM)	Brushed S.S. (SS)
-----------	----------	--------------	------------	------------	---------------	-------------------

Hinge Top without Base

Below grade wiring protection

cULus Listed: Standard 1773. Rated NEMA 3R. ADA compliant heights available.

Hinge Top without Base | 1-gang (up to 20 amp devices)

Material	304 Stainless Steel: 14-gauge body, cover and access panel; optional upgrade to 316
Construction	Welded body and weatherproof cover (lockable)
Finishes	Outdoor rated powder coat paint (standard and custom), brushed stainless
Heights	42", 48", 54" (24" must be buried below grade)
Dimensions	2-1/2" wide by 4" deep pedestal with 2-3/4" wide by 6" deep cover
Devices	Not supplied; can accommodate 15 – 20A NEMA rated receptacles (must be weather-resistant)
Device Mount	Removable GFCI device mounting plate insert included
Cover	Auto-closing cover provides protection to meet while-in-use requirements
Hardware	Pre-installed stainless steel grounding hardware included
Customization	Custom powder coat options
Installation	Open bottom, removeable wire access panel and wire entry slots

Locking stainless steel cover



Part Numbering

Device Mtg. Plate	Finish	42" Height	48" Height	54" Height
	Black	142-C-HT-B	148-C-HT-B	154-C-HT-B
	Gray	142-C-HT-G	148-C-HT-G	154-C-HT-G
	Bronze	142-C-HT-BRZ	148-C-HT-BRZ	154-C-HT-BRZ
	Green	142-C-HT-GN	148-C-HT-GN	154-C-HT-GN
	Brown	142-C-HT-BRZ	148-C-HT-BRZ	154-C-HT-BRZ
	Custom	142-C-HT-CSTM	148-C-HT-CSTM	154-C-HT-CSTM
	Brushed S.S.	142-SS-HT	148-SS-HT	154-SS-HT

All models feature


- Heavy stainless steel welded construction
- Self-closing cover prevents ingress of water from outdoor elements
- Removeable access panel for easy installation
- Locking tab to prevent unwanted use
- Wire entry side slots

Blends into landscapes and foliage



Note: The divided models have recently been discontinued. If you cannot find a part number, [click here](#) for a cross-reference alternate guide.

Finishes



5x5 Hinge Top without Base: Direct Bury

Industrial durability for in-ground use

cULus Listed: Standard 1773. Rated NEMA 3R. ADA compliant heights available.

5x5 Hinge Top without Base

1-, 2-gang (up to 60 amp devices)

Material	304 Stainless Steel: 14-gauge body, cover and access panel; optional upgrade to 316
Construction	Welded body and weatherproof cover (lockable)
Finishes	Outdoor rated powder coat paint (standard and custom), brushed stainless
Heights	42", 48", 54" (24" must be buried below grade)
Dimensions	5" wide by 5" deep pedestal with 5-1/4" wide by 6-1/4" deep cover
Devices	Not supplied; For 15-20A devices, weather-resistance devices must be used; devices that are 30-60A must be water-tight
Device Mount	Removable GFCI device mounting plate insert included
Cover	Auto-closing cover provides protection to meet while-in-use requirements for 15 and 20A devices; for aesthetics only when used with 30 - 60A devices
Hardware	Pre-installed stainless steel grounding hardware included
Application	May be ordered with a divider for high and low voltage (data)
Customization	Custom powder coat options
Installation	Open bottom, removeable wire access panel and wire entry slots

Locking stainless steel cover



Part Numbering (power only)

Device Mounting Plate	Height	Powder Coat ("C")	Brushed SS ("SS")
20A PED0140	42"	542-C-HT-*-140	542-SS-HT-140
	48"	548-C-HT-*-140	548-SS-HT-140
	54"	554-C-HT-*-140	554-SS-HT-140
30A: PED0142 (1-9/16" dia.)	42"	542-C-HT-*-142	542-SS-HT-142
	48"	548-C-HT-*-142	548-SS-HT-142
	54"	554-C-HT-*-142	554-SS-HT-142
50/60A PED0154	42"	542-C-HT-*-154	542-SS-HT-154
	48"	548-C-HT-*-154	548-SS-HT-154
	54"	554-C-HT-*-154	554-SS-HT-154
20, 30A PED0144	42"	542-C-HT-*-144	542-SS-HT-144
	48"	548-C-HT-*-144	548-SS-HT-144
	54"	554-C-HT-*-144	554-SS-HT-144
30A: PED0148 (2-1/8" dia.)	42"	542-C-HT-*-148	542-SS-HT-148
	48"	548-C-HT-*-148	548-SS-HT-148
	54"	554-C-HT-*-148	554-SS-HT-148

All models feature

- Self-closing cover prevents ingress of water from outdoor elements
- Locking hole to prohibit unauthorized access
- Removeable access panel and sides slots for wire entry for easy installation
- Completely welded stainless construction

*insert powder coat finish code:


B = black, G = gray, BRZ = bronze, GN = green, BR = brown, CSTM - custom

Note: Part numbers have recently been updated, and the side divided models have been discontinued. If you cannot find a part number, [click here](#) for a cross-reference guide.

Part Numbering (divided for high and low voltage)

Device Mounting Plate	Height	Powder Coat ("C")	Brushed SS ("SS")
20A PED0140	42"	542-C-D-HT-*-140	542-SS-D-HT-140
	48"	548-C-D-HT-*-140	548-SS-D-HT-140
	54"	554-C-D-HT-*-140	554-SS-D-HT-140
20, 30A PED0144	42"	542-C-D-HT-*-144	542-SS-D-HT-144
	48"	548-C-D-HT-*-144	548-SS-D-HT-144
	54"	554-C-D-HT-*-144	554-SS-D-HT-144

Finishes



Solidly built and will withstand harsh environments

Standard without Base

Higher amperage compatible with standard weatherproof covers

cULus Listed: Standard 1773. Rated NEMA 3R. ADA compliant heights available.

Standard without Base





1-, 2-gang (up to 60 amp devices)

Material	304 Stainless Steel: 14-gauge body, cover and access panel; optional upgrade to 316
Construction	Welded body with removeable wire access panel and wire entry slots
Finishes	Outdoor rated powder coat paint (standard and custom), brushed stainless
Heights	42", 48", 54" (24" must be buried below grade)
Dimensions	5" wide by 2-1/2" deep
Devices	Devices not supplied; 15-20A devices must be weather-resistant and used with an in-use cover; 30-60A devices must be watertight
Covers	Mounting holes for weatherproof covers provided; covers not supplied
Hardware	Pre-installed stainless steel grounding hardware included
Application	May be ordered with a divider for high and low voltage (data)
Customization	Option for custom colors
Installation	Open bottom, removeable wire access panel and wire entry slots
Receptacle Mount	Multiple device opening configurations for GFCI devices and weatherproof covers

Devices up to 60A



Part Numbering

Device Opening	Finish	42" Height	48" Height	54" Height
1-Gang Horizontal (HZ) 	Black	142-C-HZ-B	148-C-HZ-B	154-C-HZ-B
	Gray	142-C-HZ-G	148-C-HZ-G	154-C-HZ-G
	Bronze	142-C-HZ-BRZ	148-C-HZ-BRZ	154-C-HZ-BRZ
	Green	142-C-HZ-GN	148-C-HZ-GN	154-C-HZ-GN
	Brown	142-C-HZ-BR	148-C-HZ-BR	154-C-HZ-BR
	Custom	142-C-HZ-CSTM	148-C-HZ-CSTM	154-C-HZ-CSTM
	Brushed S.S.	142-SS-HZ	148-SS-HZ	154-SS-HZ
1-Gang Vertical (V) 	Black	142-C-V-B	148-C-V-B	154-C-V-BR
	Gray	142-C-V-GN	148-C-V-G	154-C-V-G
	Bronze	142-C-V-BRZ	148-C-V-BRZ	154-C-V-BRZ
	Green	142-C-V-GN	148-C-V-GN	154-C-V-GN
	Brown	142-C-V-BR	148-C-V-BR	154-C-V-BR
	Custom	142-C-V-CSTM	148-C-V-CSTM	154-C-V-CSTM
	Brushed S.S.	142-SS-V	148-SS-V	154-SS-V
2-Gang 	Black	242-C-B	248-C-B	254-C-B
	Gray	242-C-G	248-C-G	254-C-G
	Bronze	242-C-BRZ	248-C-BRZ	254-C-BRZ
	Green	242-C-GN	248-C-GN	254-C-GN
	Brown	242-C-BR	248-C-BR	254-C-BR
	Custom	242-C-CSTM	248-C-CSTM	254-C-CSTM
	Brushed S.S.	242-SS	248-SS	254-SS
2-Gang Div. (high/low voltage) 	Black	242-C-D-B	248-C-D-B	254-C-D-B
	Gray	242-C-D-G	248-C-D-G	254-C-D-G
	Bronze	242-C-D-BRZ	248-C-D-BRZ	254-C-D-BRZ
	Green	242-C-D-GN	248-C-D-GN	254-C-D-GN
	Brown	242-C-D-BR	248-C-D-BR	254-C-D-BR
	Custom	242-C-D-CSTM	248-C-D-CSTM	254-C-D-CSTM
	Brushed S.S.	242-SS-D	248-SS-D	254-SS-D

All models feature

- Mounting holes to align with standard GFCI decora style receptacle(s) and weatherproof covers
- Removeable access panel for easy installation
- Sides slots for wire entry

Before and After



Finishes

