

Specifications: Standard without Integral Base


Higher amperage compatible with standard weatherproof covers



UL Listed: Standard 1773. Rated NEMA 3R. Options that meet ADA minimum 15" receptacle height requirement.

Standard without Integral Base

1-, 2-gang (up to 60 amp devices)



Free standing power pedestals that are an aesthetically pleasing solution to safely and conveniently bring power to any outdoor location. Offering hundreds of configurations and finishes, Pedocs will blend into any landscape.

Material	304 Stainless Steel: 14-gauge body and access panel; optional upgrade to 316
Construction	Welded body with removeable wire access panel and wire entry slots
Finishes	Outdoor rated powder coat paint (standard and custom), brushed stainless
Heights	42", 48", 54" (24" must be buried below grade)
Dimensions	5" wide by 2-1/2" deep
Amperage	Accepts up to 60 amp devices
Hardware	Pre-installed SS grounding hardware included
Application	May be ordered with a divider for high and low voltage (data)
Customization	Option for custom colors
Installation	Open bottom, removeable wire access panel and wire entry slots
Receptacle Mount	Multiple device opening configurations for GFCI devices and weatherproof covers
Additional	Devices and covers not supplied

Product Highlights

- Multiple device opening configurations
- Accommodates 20 – 60 amp devices
- Removeable access panel for easy installation
- Sides slots for wire entry
- Pre-drilled mounting holes for devices and covers
- Pre-drilled mounting holes for devices and covers
- May be ordered with an internal dividing channel to separate high and low voltage
- Heavy stainless steel (SS) welded construction
- Solid construction saves on costly repair and replacement maintenance



Devices and covers not supplied



Part Numbering Guide

Example of photo above:

242-C-G


- 2 (2-gang)
- 42 (42" tall)
- C (powder coated)
- (left blank for non-divided)
- (left blank; 2-gang always vertical)
- G (gray)

Mtg. type	Hgt.	Finish type	High/low volt. divider	Device configuration	Color (coated only)
1: 1-gang 2: 2-gang	42" 48" 54"	-C: powder coated -SS: brushed	Leave blank for non-divided -D: divided	-HZ: horizontal -V: vertical Leave blank for 2-gang models	-B: black -G: gray -BRZ: bronze -GN: green -BR: brown -*CSTM: custom Leave blank for brushed finish

Device mounting configurations



Finishes



U.S.A. manufactured and 100% U.S.A. sales and tech support.

www.pedocpower.com | info@pedocpower.com | (888) 518-0330

STDWOBSSS